



Fig 115

Runko GGG40 DIN1693
Läppä Stainless steel 18/8/2
Tiiviste EPDM



DN		Runko mitat					Asennuslaipat					Akselinpää						Paino				
mm	inch.	A	B	ØC	D	E	ISO-5211/2	No	ØJ	ØK	ØL	ØM	N	O	P	ØR	S	T	U	V	"Q"	Kg
50	2"	140	83	102	12	43	F-07	4	9	70	90	55	3	26	20	13,2	10	11			32	3,3
65	2 1/2"	152	93	122	12	46	F-07	4	9	70	90	55	3	26	20	13,2	10	11			51	4
80	3"	159	98	139	12	46	F-07	4	9	70	90	55	3	26	20	13,2	10	11			69	4,3
100	4"	178	111	159	14	52	F-07	4	9	70	90	55	3	30	24	16,8	12,5	14			89	5,7
125	5"	191	127	189	14	56	F-07	4	9	70	90	55	3	30	24	16,8	12,5	14			115	7,4
150	6"	203	143	214	15	56	F-07	4	9	70	90	55	3	33	27	20,4	15	17			143	8,9
200	8"	245	172	269	15	60	F-07	4	9	70	90	55	3	33	27	20,4	15	17			194	13,5
250	10"	275	204	331	17	68	F-10	4	11	102	125	70	3	47	45	28	24	22			243	22,8
300	12"	315	242	380	17	78	F-10	4	11	102	125	70	3	47	45	28	24	22			293	31,7
350	14"	307	291	442	22	78	F-12	4	13	125	150	85	3	55		36			10	4,7	332	43,2
400	16"	342	325	493	24	102	F-14	4	17	140	175	100	4	65		42			12	4,9	382	65,2
450	18"	387	357	544	27	113	F-14	4	17	140	175	100	4	65		48			14	5,5	432	84,5
500	20"	425	381	601	27	126	F-14	4	17	140	175	100	4	65		48			14	5,5	478	119
600	24"	532	488	695	40	146	F-25	8	18	254	300	200	5	110		72			20	7,4	585	281
700	28"	573	506	798	40	175	F-25	8	18	254	300	200	5	110		72			20	7,4	683	414
750	30"	622	555	872	40	176	F-25	8	18	254	300	200	5	110		72			20	7,4	733	508
800	32"	650	578	908	40	215	F-25	8	18	254	300	200	5	110		72			20	7,4	755	572
900	36"	707	643	1004	40	246	F-25	8	18	254	300	200	5	110		98			28	9,9	852	639
1000	40"	755	729	1114	40	280	F-25	8	18	254	300	200	5	110		98			28	9,9	958	918
1050	42"	781	755	1196	40	280	F-25	8	18	254	300	200	5	110		98			28	9,9	1013	1034
1100	44"	800	774	1220	40	280	F-25	8	18	254	300	200	5	110		98			28	9,9	1050	1150
1200	48"	900	855	1330	50	360	F-30	8	22	298	350	230	5	130		120			32	11,1	1098	1760